

HUB REDESIGN NOW AVAILABLE IN 3" - 6" LEVER OPERATED AND WEIGHT OPERATED DUMP VALVES

This product notice is to inform you of a change to components in 3"-6" Lever Operated and Weight Operated Dump Valves.

We have completed the change-over from the single-D style hub and shaft connection to the new design with two flats to reduce rotational play in the connection.



In a previous notice in April 2021, we informed you that this change had been made to the 2" Lever Operated Valves.

This new change covers all the remaining sizes in the Lever Operated and Weight Operated models. This change will help consolidate parts between the two models.

You will start to see these changes soon in new assemblies of these models, some earlier than others based on current stock levels.

Below are the part numbers affected:

SHAFTS

Description	Old P/N	New P/N
2" Shaft, Standard	7404	7609*
2" Shaft, 316 SS	740S6	7609S6*
3" Shaft, Standard	7408	7610
3" Shaft, 316 SS	7408S6	7610S6
4" Shaft, Standard	7427	7611
4" Shaft, 316 SS	7427S6	7611S6
6" Shaft, Standard6"	7449	7612
Shaft, 316 SS	7449S6	7612S6

HUBS

Description	Standard and 316 SS. P/N	New P/N**
2" Hub	7403/7403S6	7613S6*
3" Hub	7407/7407S6	7614S6
4" Hub	7454/7454S6	7615S6
6" Hub	7453/7453S6	7616S6

* 2" parts already exist in Lever Operated Dump Valves and will now be installed in Weight Operated Dump Valves.

** New hubs are all 316 Stainless Steel, standard and all optional codes

This change is backwards compatible with previous versions of these valves, as long as both the hub and shaft are replaced as a set. The exception is if the valve was manufactured prior to April 2019, (serial number 2190910001) in which case it may not have a lever hub with set screw as shown here.

If this is the case, here are the parts needed:

	2"	3"	4"	6"
Lever Hub	7600	7601	7602	7603
Set Screw	7608			

