

[View this product on Kimray.com](http://kimray.com)

EUD3 230 GMT DA5-D MTR VLV

Low Pressure Control Valve | Non-Balanced | Double Acting

**2" Grooved Through Body
1.25" Equal Percentage Trim**

Process Fluid: **Liquid and Gas**
Operation: **Pneumatic**

Options Included In This Model:

- Valve Fail Position: **Closed**



Critical Flow Factor (Cf) = 0.84

100% Cv = **24.00**

Commonly used as a Burner Valve or Liquid Dump Valve for low pressure vessels

Specifications

Connection Size: **2 "**
 Connection Type: **Grooved**
 Body Style: **Through Body**
 Body Material: **Cast Ductile**
Option Available for NACE MR0175 compliance or certification.
 Trim Size: **1.25 "**
 Trim Type: **Equal Percentage**
 Seal Class: **Class VI**
 Process Fluid: **Liquid and Gas**
 Max. Working Pressure: **300 psig**
 Valve Fail Position: **Closed**
 Operation: **Pneumatic**
 Catalog Page: **E2:40.3**
 Face-to-Face Length: **8.94**
 Repair Kit P/N: **ROI**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
1.3	2.4	4	6.7	10.4	14.4	16.9	19.7	22.1	24

Flow Coefficient (CV) at Stem Travel (% Open) for Item: EUD3



