

[View this product on Kimray.com](http://www.kimray.com)

AEN 218 FGT LBP-D REGULATOR

Pressure Regulator | Back Pressure Regulator | Liquid Back Pressure - Outside Supply Required

**2" 150 RF Through Body
2" Equal Percentage Trim**

Process Fluid: **Liquid and Gas**
Operation: **Pneumatic**
Pilot Type: **Vent**




Critical Flow Factor (Cf) = 0.84

100% Cv = 47.00

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
4	6.2	8.6	12.1	17.2	23.5	30.4	36.3	42.5	47

Flow Coefficient (CV) at Stem Travel (% Open) for Item: AEN



Control pressure upstream of the valve by adjusting the set point to the desired max upstream pressure. Used on separators, heater treaters, compressor stations, and gas gathering systems.

Outside Supply of clean/dry gas or air required.

Specifications

Connection Size: **2 "**
 Connection Type: **150 RF**
 Body Style: **Through Body**
 Body Material: **Cast Ductile**
Option Available for NACE MR0175 compliance or certification.
 Trim Size: **2 "**
 Trim Type: **Equal Percentage**
 Seal Class: **Class VI**
 Process Fluid: **Liquid and Gas**
 Pilot Type: **Vent**
 Max. Working Pressure: **250 psig**
 Min. Set Point Pressure: **10 psig**
 Max. Set Point Pressure: **250 psig**
 Operation: **Pneumatic**
 Catalog Page: **A:40.3**
 Face-to-Face Length: **9**
 Repair Kit P/N: **RDG**