

[View this product on Kimray.com](#)

EEDV 2 FMVT 600RF 5/8 IV VIT

Metering Valve

**Stem Guided Non Balanced
2" 600 RF Through Body
0.625" Equal Percentage Trim**

Process Fluid: **Liquid and Gas**
Operation: **Manual**

Options Included In This Model:

- Elastomer: **FKM**



Critical Flow Factor (Cf) = 0.58

100% Cv = **10.76**

Can be used to meter or control flow of liquids and/or gases on meter runs or flow lines. It can be used as a choke under low pressure drop conditions where freezing is not a problem. Used any time a reference control point is required in 64ths of an inch opening.

Specifications

Connection Size: **2 "**
Connection Type: **600 RF**
Body Style: **Through Body**
Body Material: **Steel**
Option Available for NACE MR0175 compliance or certification.
Trim Size: **0.625 "**
Trim Type: **Equal Percentage**
Seal Class: **Class IV**
Process Fluid: **Liquid and Gas**
Max. Working Pressure: **1480 psig**
Operation: **Manual**
Catalog Page: **E1:50.3**
Face-to-Face Length: **11.25**
Repair Kit P/N: **RSE-V**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
0.3	0.5	0.9	1.1	1.4	2.3	3.9	6.4	8.7	10.76

Flow Coefficient (CV) at Stem Travel (% Open) for Item: EEDV



