

[View this product on Kimray.com](#)

EENS6V 2200 SMVT 5/8 IV S6 VITON

Metering Valve

**Stem Guided Non Balanced
2" Female NPT Through Body
0.625" Equal Percentage Trim**

Process Fluid: **Liquid and Gas**
Operation: **Manual**

Options Included In This Model:


- Elastomer: **FKM**
- Trim Material: **Stainless Steel**



Critical Flow Factor (Cf) = 0.58

100% Cv = 10.76

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
0.3	0.5	0.9	1.1	1.4	2.3	3.9	6.4	8.7	10.76



Can be used to meter or control flow of liquids and/or gases on meter runs or flow lines. It can be used as a choke under low pressure drop conditions where freezing is not a problem. Used any time a reference control point is required in 64ths of an inch opening.

Specifications

Connection Size: **2 "**
 Connection Type: **Female NPT**
 Body Style: **Through Body**
 Body Material: **Steel**
NACE MR0175 Compliant
 Trim Size: **0.625 "**
 Trim Type: **Equal Percentage**
 Seal Class: **Class IV**
 Process Fluid: **Liquid and Gas**
 Max. Working Pressure: **2000 psig**
 Operation: **Manual**
 Catalog Page: **E1:50.3**
 Face-to-Face Length: **6.56**
 Repair Kit P/N: **RSE-V**

