

[View this product on Kimray.com](#)

## EGL 3 FMVT 600RF PB 3 IV

Metering Valve

**Piston Balanced**  
**3" 600 RF Through Body**  
**3" Equal Percentage Trim**

Process Fluid: **Liquid and Gas**  
Operation: **Manual**



Can be used to meter or control flow of liquids and/or gases on meter runs or flow lines. It can be used as a choke under low pressure drop conditions where freezing is not a problem. Used any time a reference control point is required in 64ths of an inch opening.

### Specifications

Connection Size: **3 "**  
Connection Type: **600 RF**  
Body Style: **Through Body**  
Body Material: **Steel**  
**Option Available for NACE MR0175 compliance or certification.**  
Trim Size: **3 "**  
Trim Type: **Equal Percentage**  
Seal Class: **Class VI**  
Process Fluid: **Liquid and Gas**  
Max. Working Pressure: **1480 psig**  
Operation: **Manual**  
Catalog Page: **E1:55.3**  
Face-to-Face Length: **13.25**  
Repair Kit P/N: **RSO**

Critical Flow Factor (Cf) = 0.75

100% Cv = **107.00**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
4	6	10	13	16	26	54	83	97	107

Flow Coefficient (CV) at Stem Travel (% Open) for Item: EGL



