

[View this product on Kimray.com](https://www.kimray.com)

## AGH 327 FGT PR-S REGULATOR

Pressure Regulator | Pressure Reducing Regulator | Gas Pressure Reducing

**3" 150 RF Through Body**  
**3" Equal Percentage Trim**

Process Fluid: **Gas**  
Operation: **Pneumatic**  
Pilot Type: **Vent**



Critical Flow Factor (Cf) = 0.75

100% Cv = **117.00**

Control pressure downstream of the valve by adjusting the set point to the desired max downstream pressure. Commonly used as a suction control valve on compressors.

Utilizes process gas to operate integrated pilot. Gas must be clean and dry.

### Specifications

Connection Size: **3 "**  
Connection Type: **150 RF**  
Body Style: **Through Body**  
Body Material: **Steel**  
**Option Available for NACE MR0175 compliance or certification.**  
Trim Size: **3 "**  
Trim Type: **Equal Percentage**  
Seal Class: **Class VI**  
Process Fluid: **Gas**  
Pilot Type: **Vent**  
Max. Working Pressure: **285 psig**  
Min. Set Point Pressure: **10 psig**  
Max. Set Point Pressure: **285 psig**  
Operation: **Pneumatic**  
Catalog Page: **A:20.4**  
Face-toFace Length: **12.38**  
Repair Kit P/N: **RAF**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
9.9	15.6	21.5	30.2	42.9	58.6	75.7	90.4	105.7	117

Flow Coefficient (CV) at Stem Travel (% Open) for Item: AGH



