

[View this product on Kimray.com](http://www.kimray.com)

## AOSD2.55 2.2 SGT OPR5-D

Pressure Regulator | Pressure Reducing Regulator | Gas Ounces Pressure Reducing

**2" Female NPT Through Body  
1.25" Equal Percentage Trim**

Process Fluid: **Gas**  
Operation: **Pneumatic**  
Pilot Type: **Vent**



Critical Flow Factor (Cf) = 0.75

100% Cv = 21.00

Control pressure downstream of the valve by adjusting the set point to the desired max downstream pressure. Commonly used as a suction control valve on compressors.

Utilizes process gas to operate integrated pilot. Gas must be clean and dry.

### Specifications

Connection Size: **2 "**  
Connection Type: **Female NPT**  
Body Style: **Through Body**  
Body Material: **Cast Ductile**  
**Option Available for NACE MR0175 compliance or certification.**  
Trim Size: **1.25 "**  
Trim Type: **Equal Percentage**  
Seal Class: **Class VI**  
Process Fluid: **Gas**  
Pilot Type: **Vent**  
Max. Working Pressure: **300 psig**  
Min. Set Point Pressure: **0.03125 psig**  
Max. Set Point Pressure: **2.5 psig**  
Operation: **Pneumatic**  
Catalog Page: **A:110.4**  
Face-toFace Length: **8.5**  
Repair Kit P/N: **RUAD**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
1.8	2.8	3.9	5.4	7.7	10.5	13.6	16.2	19	21

Flow Coefficient (CV) at Stem Travel (% Open) for Item: AOSD2.55

