

[View this product on Kimray.com](http://kimray.com)

## AOZD5 4.5 FGT OPR-D W/5# SPRING

Pressure Regulator | Pressure Reducing Regulator | Gas Ounces Pressure Reducing

**4" 150 RF Through Body  
4" Equal Percentage Trim**

Process Fluid: **Gas**  
Operation: **Pneumatic**  
Pilot Type: **Vent**



Critical Flow Factor (Cf) = 0.75

100% Cv = **210.00**

Control pressure downstream of the valve by adjusting the set point to the desired max downstream pressure. Commonly used as a suction control valve on compressors.

Utilizes process gas to operate integrated pilot. Gas must be clean and dry.

## Specifications

Connection Size: **4 "**  
Connection Type: **150 RF**  
Body Style: **Through Body**  
Body Material: **Cast Ductile**  
**Option Available for NACE MR0175 compliance or certification.**  
Trim Size: **4 "**  
Trim Type: **Equal Percentage**  
Seal Class: **Class VI**  
Process Fluid: **Gas**  
Pilot Type: **Vent**  
Max. Working Pressure: **250 psig**  
Min. Set Point Pressure: **0.0625 psig**  
Max. Set Point Pressure: **5 psig**  
Operation: **Pneumatic**  
Catalog Page: **A:110.4**  
Face-toFace Length: **15**  
Repair Kit P/N: **RUCD**

Cv @ % Stem Travel (%open)									
10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
17.8	27.9	38.6	54.2	77	105.2	135.9	162.2	189.8	210

Flow Coefficient (CV) at Stem Travel (% Open) for Item: AOZD5

