

Series:
CV = Control Valves

Model:
C = Cage Guided

Line Size:
2 = 2 NPS
3 = 3 NPS
4 = 4 NPS
6 = 6 NPS
8 = 8 NPS
0 = 10 NPS

End Connection:
2" 3", 4", 6", 8" & 10"

Body Type:
T = Thru

Shell Material:
W = WCB Steel *

Trim Type:
FEP = Equal Percentage
FQK = Quick Open
REP = Reduced E.P.

Actuator:

Service Type:

	Plug	Cage	Seat
S = Standard	D2	S6	D2
C = Corrosive	S6	S6	S6
K = Corrosive with Coating			
E = Erosive	ZR	S6	D2

0 = No Actuator
1 = 3 - 15 psi Spring Fail Close
2 = 6 - 30 psi Spring Fail Close
3 = 9 - 45 psi Spring Fail Close
4 = 3 - 15 psi Spring Fail Open
5 = 6 - 30 psi Spring Fail Open
6 = 9 - 45 psi Spring Fail Open
8 = Metering Valve (2"-4" only)

CV C 2 S2 T W FEP 2 S

Not all selections available on all products listed.
See product pages 01:20.1 - 01:20.3 for available options

Options: Additional cost and lead times will apply
If multiple options required input in sequential order
Leave blank if no options required

- 1 = NACE Certification (Corrosive Option Only)
- 2 = Hydrostatic Test Certification
- 3 = MTR (Shell Components)
- A = AFLAS Elastomers
- E = VEE Packing
- G = Graphite Vee Packing
- H = HSN Elastomers
- V = FKM Elastomers
- X = Export (Hydrostatic test, MTR & 3.1)

* Other materials available upon request