

# LIQUID DUMP VALVES LEVER OPERATED



## CODE BUILDER D SERIES

Series:

**D = Dump Valve**

Model:

**LD = Lever Operated Diaphragm Balanced**

LP = Lever Operated Piston Balanced Throttle (2 & 3 inch only)

LB = Lever Operated Piston Balanced (2, 3 & 4 inch only)

Line Size:

**2 = 2 NPS**

3 = 3 NPS

4 = 4 NPS

6 = 6 NPS

End Connection:

**SA = FNPT (2 & 3 NPS only)**

AR = 150RF

Body Type:

**A = Angle**

T = Thru

Shell Material:

**D = Ductile Iron**

**E = Ductile Iron w/Coating**

Inner Valve Size:

**F = Full Port**

R = Reduced Port (LP only)

Actuator:

**L = Lever Operated**

Service Type:

**S = Standard**

C = Corrosive

LP Model: Corrosive is only available in 2"

D	LD	2	SA	A	D	F	L	S	
---	----	---	----	---	---	---	---	---	--

Options: Additional cost and lead times will apply

If multiple options required input in sequential order

Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)

2 = Hydrostatic Test Certification

3 = MTR (Shell Components)

H = HSN Elastomers

V = FKM Elastomers

X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.  
See product pages 03:10.1 - 03:20.7 for available options