

# LIQUID DUMP VALVES PNEUMATIC OPERATED



## CODE BUILDER D SERIES

Series:

**D = Dump Valve**

Model:

**PD = Pneumatic Operated Diaphragm Balanced**

PP = Pneumatic Operated Piston Balanced Throttle 4" only

Line Size:

**2 = 2 NPS**

3 = 3 NPS

4 = 4 NPS

6 = 6 NPS (PD ONLY)

End Connection:

**SA = FNPT (2 & 3 NPS only)**

AR = 150RF

Body Type:

**A = Angle**

T = Thru

Shell Material:

**D = Ductile Iron**

Inner Valve Size:

**F = Full Port**

R = Reduced Port (PP only)

Actuator:

**1 = Pneumatic Fail Close**

4 = Pneumatic Fail Open

Service Type:

**S = Standard**

C = Corrosive

K = Corrosive with Coated Shell Components

D	PD	2	SA	A	D	F	1	S	
---	----	---	----	---	---	---	---	---	--

Options: Additional cost and lead times will apply

If multiple options required input in sequential order

Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)

2 = Hydrostatic Test Certification

3 = MTR (Shell Components)

H = HSN Elastomers

V = FKM Elastomers

X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.  
See product pages 04:10.1 - 04:10.7 & 04:30.1 - 04:40.7  
for available options