

PRESSURE REGULATORS



CODE BUILDER SPRING LOADED R SERIES

Series:

R = Pressure Regulator

Model:

SB = Spring Loaded BP

Line Size:

2 = 2 NPS

3 = 3 NPS

End Connection:

SA = FNPT

AR = 150RF Flange

GV = Grooved (2 NPS only)

Shell Material:

D = Ductile Iron

E = Ductile Iron w/Coating

W = Steel (WCB)

X = Steel (WCB) w/Coating

Inner Valve Size:

F = Full Port

R = Reduced Port

Control Range:

Service Type:

S = Standard

C = Corrosive

Spring Loaded 2"	A =	Full Port	Reduced Port
		0-10 psig	0-10 psig
		10-20 psig	10-20 psig
		15-30 psig	20-40 psig
		25-50 psig	40-65 psig
		30-65 psig	65-90 psig
		40-85 psig	80-125 psig
3"	G =	10-75 psig	N/A

R SB 2 SA D F A S

Options: Additional cost and lead times will apply
If multiple options required input in sequential order
Leave blank if no options required

- 1 = NACE Certification (Corrosive Option Only)
- 2 = Hydrostatic Test Certification
- 3 = MTR (Shell Components)
- A = AFLAS Elastomers
- H = HSN Elastomers
- V = FKM Elastomers
- X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.
See product pages 06:100.1 - 06:100.11 for available options