CODE BUILDER
SPRING LOADED R SERIES

Series:
- **R = Pressure Regulator**

Model:
- SB = Spring Loaded BP

Line Size:
- **2 = 2 NPS**
- 3 = 3 NPS

End Connection:
- **SA = FNPT**
- AR = 150RF Flange
- GV = Grooved (2 NPS only)

Shell Material:
- **D = Ductile Iron**
- W = Steel (WCB)

Inner Valve Size:
- **F = Full Port**
- R = Reduced Port

Control Range:

			Full Port	Reduced Port
Spring Loaded	2"	A =	0-10 psig	0-10 psig
		B =	10-20 psig	10-20 psig
		C =	15-30 psig	20-40 psig
		D =	25-50 psig	40-65 psig
		E =	30-65 psig	65-90 psig
		F =	40-85 psig	80-125 psig
	3"	G =	10-75 psig	N/A

Service Type:
- **S = Standard**
- C = Corrosive
- K = Corrosive with Coated Shell Components

R	SB	2	SA	D	F	A	S	

Options: Additional cost and lead times will apply
If multiple options required input in sequential order
Leave blank if no options required

- 1 = NACE Certification (Corrosive Option Only)
- 2 = Hydrostatic Test Certification
- 3 = MTR (Shell Components)
- A = AFLAS Elastomers
- H = HSN Elastomers
- V = FKM Elastomers
- X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.
See product pages 06:100.1 - 06:100.11 for available options