

Series:

F = Float Operated Controllers

Model:

PS = Pneumatic Level Switch
 PK = Pneumatic Level Switch w/o Relay
 PX = Pneumatic Extended Level Switch
 ES = Electric Level Switch
 EL = Electric Level Switch Low power
 EV = Electric Level Switch Vertical Float

Connection Size:

1 = 1 1/2 NPS (ES, EL & EV only)
 2 = 2 NPS

End Connection:

S4 = MNPT

Override:

W = With manual Override
 N = Without Manual Override

Float Type:

P = Poly - 5000 psi (ES, EL & EV only)
 S = 316SS - 2000 psi

Float Extensions:

A = None

Service Type:

S = Standard

| | | | | | | | | |
|---|----|---|----|---|---|---|---|--|
| F | PS | 2 | S4 | W | P | A | S | |
|---|----|---|----|---|---|---|---|--|

Options: Additional cost and lead times will apply
 If multiple options required input in sequential order
 Leave blank if no options required

1 = NACE Certification
 2 = Hydrostatic Test Certification
 3 = MTR (Shell Components)
 A = AFLAS Elastomers
 H = HSN Elastomer
 X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.
 See product pages 08:50.1 - 08:60.3 for available options