

## LOW PRESSURE HIGH VOLUME VALVE

This product notice is to inform you that the Low Pressure High Volume Valve is now available in 3" Reduced Port.

This means all sizes are now available:

- 2" full (Cv 54)
- 2" reduced (Cv 29)
- 3" full (Cv 109)
- 3" reduced (Cv 72)

This includes both angled body and thru body, with threaded connections and 150RF flanged connections for ALL sizes!

In the charts below you will find the Valve, Repair Kit, and Plug Assembly codes to order.

Elastomers are HSN standard, with optional Viton (add V to the end of the code).

All sizes have 3 trim options: Standard Trim, D2 hardened steel trim steel trim for erosive conditions (add D2 to the end of the code), or 316 Stainless Steel trim for corrosive environments (add S6 to the end of the code).

All LPHV valves come standard in Fail Closed configuration, and are field reversible. You can order any of these configured Fail Open (add PC to code).

Size & Trim	Code	Description
2" Full	MYA	250 SMA-D LPHV
2" Reduced	MYA5	250 SMA-5-D LPHV
2" Full	MYB	225 FMA-D LPHV
2" Reduced	MYB5	225 FMA-5-D LPHV
2" Full	MYC	250 SMT-D LPHV
2" Reduced	MYC5	250 SMT-5-D LPHV
2" Full	MYD	225 FMT-D LPHV
2" Reduced	MYD5	225 FMT-5-D LPHV
3" Full	MYE	350 SMA-D LPHV
3" Reduced	MYE5	350 SMA-5-D LPHV
3" Full	MYF	325 FMA-D LPHV
3" Reduced	MYF5	325 FMA-5-D LPHV
3" Full	MYG	350 SMT-D LPHV
3" Reduced	MYG5	350 SMT-5-D LPHV
3" Full	MYH	325 FMT-D LPHV
3" Reduced	MYH5	325 FMT-5-D LPHV

Size & Trim	Repair Kit	Plug Assembly
2" Full	RYW	MYJ
2" Reduced	RYW5	MYI
3" Full	RYX	MYK
3" Reduced	RYX5	MYL

Check out the Field Study we recently published about how the LPHV valve could be a great benefit to your wellsite.  
<https://kimray.com/training/field-study-low-pressure-high-volume-valve-bakken>

Need Quick Tip and Repair Videos?



Search for **Kimray Inc.** on Youtube