

LIQUID DUMP VALVES LEVER OPERATED



CODE BUILDER D SERIES

Series:

D = Dump Valve

Model:

LD = Lever Operated Diaphragm Balanced

LP = Lever Operated Piston Balanced Throttle (2 & 3 inch only)

LB = Lever Operated Piston Balanced

Line Size:

2 = 2 NPS

3 = 3 NPS

4 = 4 NPS

6 = 6 NPS

End Connection:

SA = FNPT (2 & 3 NPS only)

AR = 150RF

Body Type:

A = Angle

T = Thru

Shell Material:

D = Ductile Iron

Inner Valve Size:

F = Full Port

R = Reduced Port (LP only)

Actuator:

L = Lever Operated

Service Type:

S = Standard

C = Corrosive

K = Corrosive with Coated Shell Components

D	LD	2	S	A	D	F	L	S	
---	----	---	---	---	---	---	---	---	--

Options: Additional cost and lead times will apply

If multiple options required input in sequential order

Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)

2 = Hydrostatic Test Certification

3 = MTR (Shell Components)

H = HSN Elastomers

V = FKM Elastomers

X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.
See product pages 03:10.1 - 03:20.7 for available options