

# FLOAT OPERATED CONTROLLERS



## CODE BUILDER

### F SERIES (LEVEL CONTROLS)

#### Series:

F = Float Operated Controllers

#### Model:

PC = Pneumatic Level Controller

EC = Electric Level Controller (BM only)

#### Connection Size:

2 = 2 NPS

3 = 3 NPS

4 = 4 NPS

5 = 5 NPS (HU only)

6 = 6 NPS

#### End Connection:

S4 = 4000 psi MNPT - 2 inch only

AR = 150 RF

BR = 300 RF

DR = 600 RF

ER = 900 RF

FR = 1500 RF

DJ = 600 RTJ

EJ = 900 RTJ

FJ = 1500 RTJ

HU = Hammer Union - 3,4,5 inch only

GV = Grooved - 2 inch L & R only

#### Mounting Type:

L = Left Side Mount

R = Right Side Mount

B = Back Mount

#### Displacer Type:

#### Displacer Extensions:

A = None

B = 6 inch

C = 12 inch

D = 18 inch

1 = 1 7/8 x 12

2 = 1 7/8 x 20

3 = 3 x 12

4 = 2 1/2 x 12

5 = 1 7/8 x 5 11/16

6 = 1 3/4 x 12

7 = 1 3/4 x 20

Poly  
4000 psi

316SS  
2000 psi

#### Service Type:

S = Standard LCC body)

C = Corrosive (S6 body)

F	PC	2	S4	B	1	A	S	
---	----	---	----	---	---	---	---	--

Options: Additional cost and lead times will apply

If multiple options required input in sequential order

Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)

2 = Hydrostatic Test Certification

3 = MTR (Shell Components)

A = AFLAS Elastomer

H = HSN Elastomer

X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.  
See product pages 08:10.1 - 08:30.3 for available options