

PRODUCT DESCRIPTIONS (Model / Item Number)

230 SGT BP-D

2 2" CONNECTION
30 300 PSIG
S NPT
G NON-BLEED PILOT REGULATOR
T THROUGH
BP BACK PRESSURE
D CAST DUCTILE

LINE SIZE

PSIG WORKING PRESSURE (MULTIPLY BY 10)*

CONNECTION	TYPE	BODY STYLE	SERVICE	BODY MATERIAL
S NPT <i>(Screwed)</i> F FLANGED G GROOVED	G NON-BLEED PILOT REGULATOR O FLOAT-OPERATED VALVE W TREATER VALVE <i>(Weight-Operated)</i> M MOTOR VALVE <i>(Control Valve)</i> L PILOT LIQUID VALVE	A ANGLE T THROUGH D DUAL 3W 3 WAY <i>(discontinued)</i>	BP BACK PRESSURE PR PRESSURE REDUCING BPOS BACK PRESSURE OUTSIDE SUPPLY PROS PRESSURE REDUCING OUTSIDE SUPPLY PD PRESSURE DIFFERENTIAL VAC VACUUM PRB PRESSURE REDUCING-BALANCED PO PRESSURE OPENING PC PRESSURE CLOSING	D CAST DUCTILE S STEEL S6 STAINLESS STEEL TRIM 5 REDUCED PORT [CXA5 250 SOA PBT-D-5 O/W MYA5 250 SMA-5-D LPHV]

ORDER CODE (Item Code / Product Code)



AAR

Description:
230 SGT BP-D REG

VS



AARS6HSNNCMTR

Description:
230 SGT BP-D REG

STANDARD CODE	TRIM MATERIAL	ELASTOMER	COATING	CERTIFICATION
AAR BACK PRESSURE REGULATOR	S6 STAINLESS STEEL	HSN HSN AF AFLAS V VITON	KC KIMCOAT	NC NACE <i>(National Association of Corrosion Engineers)</i> MTR MATERIAL TEST REPORT HY HYDROSTATIC TESTING

SERIAL NUMBER (2003-current)

209 015 1152

Year (209 = 2009)

Day of the year

Number relative to the total number of products built that day

KIMRAY INC.

@KimrayInc

*Does not apply to all products. Different product categories may have rule exceptions.